MODEL NO. GRIP.10100.20

Standards:

ASTM D624 - 07 ASTM D751 - 11

ASTM D828 - 02 ASTM D882 - 18

ASTM D953 - 19 ASTM D1000 - 99 ASTM D1593 - 19

ASTM D5378 - 00

Material Type:

PLASTIC, FABRICS, FILM, VINYL


Type of Testing:

TENSILE, GRIPS, MECHANICAL

200 LBS SCREW ACTION GRIPS WITH GRIP FACES







Model No.	Specimen Size or Difference Between Fixtures	<u>Construction</u>	<u>Temperature</u>
GRIP.10100.20	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D0751.10	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D0882.10	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D0953.10	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D1000.10	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D1593.10	1" by 1" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D0751.40	1" by 2" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D5034.10	1" by 2" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
ASTM.D5378.10	1" by 2" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
	, ,		,
ASTM.D0751.50	1" by 3" grip faces	Aluminum and steel	-20 to 120°F (-29 to 49°C)
	, , ,		,
ASTM.D0828.10	1" by 1" line contact grip face	Aluminum and steel	-20 to 120°F (-29 to 49°C)

Fixture: Mounting (2) 1/2"-20 threaded stud and locking nuts

Capacity 200 lbs (900N)
Weight 5 lbs approximately
Dimensions Assembled - 2" x 5" x 10"

Standard Manufactured in compliance with ASTM D624, D828, D882, D953, D1000, D1593,

D5034 and D5378

QUOTE

Model No. GRIP.10100.20 - 200 lbs Screw Action Grip Set with 1" x 1" Faces

Includes 1" x 1" flat square grip faces - The grips include two aluminum housings with a black anodized finish, and two screw-cam assemblies, which move the grip faces in and out. Supplied with (2) 1/2"-20 threaded stud and locking nut. Constructed of aluminum and steel with a protective finish. Manufactured in compliance with ASTM D624, D751, D882, D1000 and D1593.

Model No. ASTM.D5034.10 - 200 lbs Screw Action Grip Set 1" x 2" Faces

Includes 1" x 2" flat square grip faces - The grips include two aluminum housings with a black anodized finish, and two screw-cam assemblies, which move the grip faces in and out. Supplied with (2) 1/2"-20 threaded stud and locking nut. Constructed of aluminum and steel with a protective finish. Manufactured in compliance with ASTM D751, D5034 and D5378.

Model No. ASTM.D0751.50 - 200 lbs Screw Action Grip Set 1" x 3" Faces

Includes 1" x 3" flat square grip faces - The grips include two aluminum housings with a black anodized finish, and two screw-cam assemblies, which move the grip faces in and out. Supplied with (2) 1/2"-20 threaded stud and locking nut. Constructed of aluminum and steel with a protective finish. Manufactured in compliance with ASTM D751.

Model No. ASTM.D0828.10 - 200 lbs Screw Action Grip Set with 1" x 1" Line Contact Faces

Includes 1" x 1" two line perpendicular contact square grip faces - The grips include two aluminum housings with a black anodized finish, and two screw-cam assemblies, which move the grip faces in and out. Supplied with (2) 1/2"-20 threaded stud and locking nut. Constructed of aluminum and rubber with a protective finish. Manufactured in compliance with ASTM D828

ACCESSORIES

Model No. FAC.10100.2012 - Set of (4) 1" x 2" Flat Grip Faces for GRIP.10100.20 Model No. FAC.10100.2022 - Set of (4) 2" x 2" Flat Grip Faces for GRIP.10100.20 Model No. FAC.10100.2013 - Set of (4) 1" x 3" Flat Grip Faces for GRIP.10100.20 Model No. FAC.10100.2014 - Set of (4) 1" x 4" Flat Grip Faces for GRIP.10100.20

SPARE PARTS

Model No. FAC.10100.2011 - Extra Set of (4) 1" x 1" Flat Grip Faces for GRIP.10100.20

Model No. SPA.D0828.1001 - Set of (4) 1" x 1" Two Line Perpendicular Line Contact Grip Faces

COMMON SIZE ADAPTERS

Upper and Lower Mounting: 1/2"-20 Stud and Locking Nut

Model No. M01C21 - 1/2" Male Clevis to 1/2"-20 Coupling Model No. M02C21 - 5/8" Male Clevis to 1/2 -20 Coupling Model No. M03C21 - 1.25" Male Clevis to 1/2"-20 Coupling Model No. M12C21 - 12mm Male Clevis to 1/2"-20 Coupling Model No. S36C21 - 1"-14 Stud to 1/2"-20 Coupling

EXTRA PHOTOS:

